


DESCRIPTION The 2SA952 is designed for use in output stage of portable radio and cassette type tape recorder, general purpose applications.

- FEATURES**
- High total power dissipation.
 $P_T = 600$ mW
 - High h_{FE} and low $V_{CE(sat)}$.
 h_{FE} ($I_C = -100$ mA) : 200 TYP.
 $V_{CE(sat)}$ (-700 mA) : -0.25 V TYP.

ABSOLUTE MAXIMUM RATINGS

- Maximum Temperatures
- Storage Temperature -55 to $+150$ °C
 - Junction Temperature $+150$ °C Maximum
- Maximum Power Dissipation ($T_a = 25$ °C)
- Total Power Dissipation 600 mW
- Maximum Voltages and Currents ($T_a = 25$ °C)
- V_{CBO} Collector to Base Voltage -30 V
 - V_{CEO} Collector to Emitter Voltage -25 V
 - V_{EBO} Emitter to Base Voltage -5.0 V
 - I_C Collector Current -700 mA
 - I_B Base Current -150 mA



ELECTRICAL CHARACTERISTICS ($T_a = 25$ °C)

| SYMBOL | CHARACTERISTIC | MIN. | TYP. | MAX. | UNIT | TEST CONDITIONS |
|-----------------|-------------------------------|--------|---------|--------|------|---|
| h_{FE1}^* | DC Current Gain | 90 | 200 | 400 | — | $V_{CE} = -1.0$ V, $I_C = -100$ mA |
| h_{FE2}^* | DC Current Gain | 50 | 100 | | — | $V_{CE} = -1.0$ V, $I_C = -700$ mA |
| C_{ob} | Collector to Base Capacitance | | 17 | 40 | pF | $V_{CB} = -6.0$ V, $I_E = 0$ $f = 1.0$ MHz |
| f_T | Gain Bandwidth Product | 50 | 160 | | MHz | $V_{CE} = -6.0$ V, $I_E = 10$ mA |
| V_{BE}^* | Base to Emitter Voltage | -600 | -640 | -700 | mV | $V_{CE} = -6.0$ V, $I_C = -10$ mA |
| $V_{CE(sat)}^*$ | Collector Saturation Voltage | | -0.25 | -0.6 | V | $I_C = -700$ mA, $I_B = -70$ mA |
| $V_{BE(sat)}^*$ | Base Saturation Voltage | | -0.95 | -1.2 | V | $I_C = -700$ mA, $I_B = -70$ mA |
| I_{CBO} | Collector Cutoff Current | | | -100 | nA | $V_{CB} = -30$ V, $I_E = 0$ |
| I_{EBO} | Emitter Cutoff Current | | | -100 | nA | $V_{EB} = -5.0$ V, $I_C = 0$ |










*Pulsed PW ≤ 350 μ s, duty cycle ≤ 2.0 %

Classification of h_{FE1}

| Rank | M | L | K |
|-------|----------|-----------|-----------|
| Range | 90 - 180 | 135 - 270 | 200 - 400 |

h_{FE} Test Conditions : $V_{CE} = -1.0$ V, $I_C = -100$ mA

TYPICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$ unless otherwise noted)



EMITTER TO BASE AND COLLECTOR TO BASE CAPACITANCE vs. REVERSE VOLTAGE

