



Bridge Rectifiers



Features

- UL recognition, file #E230084
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

Mechanical Data

- **Package:** D3K
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	D2UB05A	D2UB10A	D2UB20A	D2UB40A	D2UB60A	D2UB80A	D2UB100A
Device marking code				D2UB05A	D2UB10A	D2UB20A	D2UB40A	D2UB60A	D2UB80A	D2UB100A
Repetitive peak reverse voltage		VRRM	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load	With heatsink T _C =140℃	I _O	A	2.0						
	Without heatsink T _A =29℃			1.2						
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, T _j =25℃		IFSM	A	75						
Current squared time @1ms≤t≤8.3ms T _j =25℃, Rating of per diode		I ² t	A ² s	23						
Storage temperature		T _{stg}	℃	-55 ~+150						
Junction temperature		T _j	℃	-55 ~+150						
Dielectric strength @ Terminals to case, AC 1 minute		V _{dis}	KV	2						
Mounting torque @Recommend torque: 5kg • cm		Tor	kg • cm	8						

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	D2UB05A	D2UB10A	D2UB20A	D2UB40A	D2UB60A	D2UB80A	D2UB100A
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =1.0A	1.05						
Maximum DC reverse current at rated DC blocking voltage per diode	I _{RRM}	μA	V _{RM} =V _{RRM}	5						



D2UB05A THRU D2UB100A

■ Thermal Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	D2UB05A	D2UB10A	D2UB20A	D2UB40A	D2UB60A	D2UB80A	D2UB100A
Thermal resistance	Between junction and ambient, Without heatsink	$R_{\theta J-A}$	$^{\circ}\text{C}/\text{W}$	55						
	Between junction and case, With heatsink	$R_{\theta J-C}$		1.5						

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
D2UB05A -D2UB100A	B1	Approximate 1.358	25	1500	6000	TUBE
D2UB05A -D2UB100A	A1	Approximate 1.358	500	500	9000	BOX

■ Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage






FIG4:Typical Reverse Characteristics





D2UB05A THRU D2UB100A

■ Outline Dimensions



D3K		
Dim	Min	Max
A	13.30	14.30
B	10.30	11.30
C	6.40	7.40
D	4.50	5.50
E	1.05	1.45
F	0.60	0.85
G	3.70	3.90
H	13.10	13.50
I	2.60	3.60
J	3.10	3.40
K	2.00	2.20
L	0.40	0.60



D2UB05A THRU D2UB100A

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.