


## FEATURES

- Low Supply Current . . . 85  $\mu$ A Typ
- Low Offset Voltage . . . 2 mV Typ
- Low Input Bias Current . . . 2 nA Typ
- Input Common Mode to GND
- Wide Supply Voltage . . . 3 V <  $V_{CC}$  < 32 V
- Pin Compatible With LM324
- Applications
  - LCD Displays
  - Portable Instrumentation
  - Sensor/Metering Equipment
  - Consumer Electronics (MP3 Players, Toys, Etc.)
  - Power Supplies

D, N, OR PW PACKAGE  
(TOP VIEW)



## DESCRIPTION/ORDERING INFORMATION

The LP324 and LP2902 are quadruple low-power operational amplifiers especially suited for battery-operated applications. Good input specifications and wide supply-voltage range still are achieved, despite the ultra-low supply current. Single-supply operation is achieved with an input common-mode range that includes GND.


The LP324 and LP2902 are ideal in applications where wide supply voltage and low power are more important than speed and bandwidth. These applications include portable instrumentation, LCD displays, consumer electronics (MP3 players, toys, etc.), and power supplies.

## ORDERING INFORMATION

| $T_A$         | PACKAGE <sup>(1)</sup> |              | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---------------|------------------------|--------------|-----------------------|------------------|
| 0°C to 70°C   | PDIP – N               | Tube of 25   | LP324N                | LP324N           |
|               | SOIC – D               | Tube of 50   | LP324D                | LP324            |
|               |                        | Reel of 2500 | LP324DR               |                  |
|               | TSSOP – PW             | Tube of 90   | LP324PW               | LP324            |
| Reel of 2000  |                        | LP324PWR     |                       |                  |
| –40°C to 85°C | PDIP – N               | Tube of 25   | LP2902N               | LP2902N          |
|               | SOIC – D               | Tube of 50   | LP2902D               | LP2902           |
|               |                        | Reel of 2500 | LP2902DR              |                  |
|               | TSSOP – PW             | Tube of 50   | LP2902PW              | LP2902           |
|               |                        | Reel of 2500 | LP2902PWR             |                  |

(1) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).

## SYMBOL (EACH AMPLIFIER)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**SCHEMATIC (EACH AMPLIFIER)**



**Absolute Maximum Ratings<sup>(1)</sup>**

over operating free-air temperature range (unless otherwise noted)

|   |   | MIN        | MAX       | UNIT |
|---|---|------------|-----------|------|
| V <sub>CC</sub>   | Supply voltage range <sup>(2)</sup>         |            | ±16 or 32 | V    |
| V <sub>ID</sub>   | Differential input voltage <sup>(3)</sup>   |            | ±32       | V    |
| V <sub>I</sub>  | Input voltage (either input)                | -0.3       | 32        | V    |
| Duration of output short circuit (one amplifier) to ground at (or below) T <sub>A</sub> = 25°C, V <sub>CC</sub> ≤ 15 V <sup>(4)</sup> |   |            | Unlimited |      |
| θ <sub>JA</sub>   | Package thermal impedance <sup>(5)(6)</sup> | D package  |           | °C/W |
|   |   | N package  |           |      |
|   |   | PW package |           |      |
| T <sub>J</sub>  | Operating virtual junction temperature      |            | 150       | °C   |
| T <sub>stg</sub>  | Storage temperature range                   | -65        | 150       | °C   |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltage values (except differential voltages and V<sub>CC</sub> specified for the measurement of I<sub>OS</sub>) are with respect to the network GND.
- (3) Differential voltages are at IN+, with respect to IN-.
- (4) Short circuits from outputs to V<sub>CC</sub> can cause excessive heating and eventual destruction.
- (5) Maximum power dissipation is a function of T<sub>J(max)</sub>, θ<sub>JA</sub>, and T<sub>A</sub>. The maximum allowable power dissipation at any allowable ambient temperature is P<sub>D</sub> = (T<sub>J(max)</sub> - T<sub>A</sub>)/θ<sub>JA</sub>. Operating at the absolute maximum T<sub>J</sub> of 150°C can affect reliability.
- (6) The package thermal impedance is calculated in accordance with JESD 51-7.

**ESD Protection**

| TEST CONDITIONS  | TYP | UNIT |
|------------------|-----|------|
| Human-Body Model | ±2  | kV   |

## Electrical Characteristics

$T_A = 25^\circ\text{C}$ ,  $V_{CC} = 5\text{ V}$ ,  $V_{IC} = V_{CC}/2$ ,  $R_L = 100\text{ k}\Omega$  to GND (unless otherwise noted)

| PARAMETER                                  | TEST CONDITIONS <sup>(1)</sup>   | $T_A$ <sup>(2)</sup> | LP324          |                    | LP2902         |                              | UNIT          |
|--|--|----------------------|----------------|--------------------|----------------|------------------------------|---------------|
|  |  |                      | MIN            | TYP <sup>(3)</sup> | MAX            | MIN                          |               |
| $V_{IO}$ Input offset voltage              |  | 25°C                 | 2              | 4                  | 2              | 4                            | mV            |
|  |  | Full range           |                | 9                  |                | 10                           |               |
| $I_{IB}$ Input bias current                |  | 25°C                 | 2              | 10                 | 2              | 20                           | nA            |
|  |  | Full range           |                | 20                 |                | 40                           |               |
| $I_{IO}$ Input offset current              |  | 25°C                 | 0.2            | 2                  | 0.5            | 4                            | nA            |
|  |  | Full range           |                | 4                  |                | 8                            |               |
| $A_V$ Large-signal voltage gain            | $R_L = 10\text{ k}\Omega$ to GND,<br>$V_{CC} = 30\text{ V}$                  | 25°C                 | 50             | 100                | 40             | 70                           | V/mV          |
|  |  | Full range           | 40             |                    | 30             |                              |               |
| CMRR Common-mode rejection ratio           | $V_{CC} = 30\text{ V}$ ,<br>$V_{IC} = 0\text{ V}$ to $V_{CC} - 1.5\text{ V}$ | 25°C                 | 80             | 90                 | 80             | 90                           | dB            |
|  |  | Full range           | 75             |                    | 75             |                              |               |
| $k_{VSR}$ Power-supply rejection ratio     | $V_{CC} = 5\text{ V}$ to $30\text{ V}$                                       | 25°C                 | 80             | 90                 | 80             | 90                           | V             |
|  |  | Full range           | 75             |                    | 75             |                              |               |
| $I_{CC}$ Supply current                    | $R_L = \infty$   | 25°C                 | 85             | 150                | 85             | 150                          | $\mu\text{A}$ |
|  |  | Full range           |                | 250                |                | 275                          |               |
| $V_{OH}$ Output voltage swing (high)       | $I_L = 0.35\text{ mA}$ to GND,<br>$V_{IC} = 0\text{ V}$                      | 25°C                 | 3.4            | 3.6                | 3.4            | 3.6                          | V             |
|  |  | Full range           | $V_{CC} - 1.9$ |                    | $V_{CC} - 1.9$ |                              |               |
| $V_{OL}$ Output voltage swing (low)        | $I_L = 0.35\text{ mA}$ from $V_{CC}$ ,<br>$V_{IC} = 0\text{ V}$              | 25°C                 | 0.82           | 0.7                | 0.82           | 0.7                          | V             |
|  |  | Full range           | 1              |                    | 1              |                              |               |
| $I_O$ Output source current                | $V_O = 3\text{ V}$ , $V_{ID} = 1\text{ V}$                                   | 25°C                 | 7              | 10                 | 7              | 10                           | mA            |
|  |  | Full range           | 4              |                    | 4              |                              |               |
| $I_O$ Output sink current                  | $V_O = 1.5\text{ V}$ , $V_{ID} = -1\text{ V}$                                | 25°C                 | 4              | 5                  | 4              | 5                            | mA            |
|  |  | Full range           | 3              |                    | 3              |                              |               |
|  | $V_O = 1.5\text{ V}$ , $V_{ID} = -1\text{ V}$ ,<br>$V_{IC} = 0\text{ V}$     | 25°C                 | 2              | 4                  | 2              | 4                            |               |
|  |  | Full range           | 1              |                    | 1              |                              |               |
| $I_{OS,GND}$ Output short to GND           | $V_{ID} = 1\text{ V}$  | 25°C                 | 20             | 35                 | 20             | 35                           | mA            |
|  |  | Full range           |                | 40                 |                | 40                           |               |
| $I_{OS,VCC}$ Output short to $V_{CC}$      | $V_{ID} = -1\text{ V}$   | 25°C                 | 15             | 30                 | 15             | 30                           | mA            |
|  |  | Full range           |                | 45                 |                | 45                           |               |
| $\infty V_{IO}$ Input offset voltage drift |  | 25°C                 | 10             |                    | 10             | $\mu\text{V}/^\circ\text{C}$ |               |
| $\infty I_{IO}$ Input offset current drift |  | 25°C                 | 10             |                    | 10             | $\text{pA}/^\circ\text{C}$   |               |

(1) For full-range temperature limits:  $V_{CC} = 3\text{ V}$  to  $32\text{ V}$ ,  $V_{ICR} = 0\text{ V}$  to  $V_{CC} - 1.5\text{ V}$  (unless otherwise noted)

(2) Full range is  $0^\circ\text{C}$  to  $70^\circ\text{C}$  for LP324 and  $-40^\circ\text{C}$  to  $85^\circ\text{C}$  for LP2902.

(3) All typical values are at  $T_A = 25^\circ\text{C}$ .

## Operating Conditions

$V_{CC} = \pm 15\text{ V}$ ,  $T_A = 25^\circ\text{C}$

| PARAMETER |                        | TYP | UNIT |
|-----------|------------------------|-----|------|
| GBW       | Gain bandwidth product | 100 | kHz  |
| SR        | Slew rate              | 50  | V/ms |

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| LP2902D          | ACTIVE        | SOIC         | D               | 14   | 50          | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LP2902                  | <a href="#">Samples</a> |
| LP2902DR         | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LP2902                  | <a href="#">Samples</a> |
| LP2902N          | ACTIVE        | PDIP         | N               | 14   | 25          | RoHS & Green    | NIPDAU                               | N / A for Pkg Type   | -40 to 85    | LP2902N                 | <a href="#">Samples</a> |
| LP2902PW         | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LP2902                  | <a href="#">Samples</a> |
| LP2902PWR        | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LP2902                  | <a href="#">Samples</a> |
| LP2902PWRE4      | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | LP2902                  | <a href="#">Samples</a> |
| LP324D           | ACTIVE        | SOIC         | D               | 14   | 50          | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | LP324                   | <a href="#">Samples</a> |
| LP324DR          | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green    | NIPDAU   SN                          | Level-1-260C-UNLIM   | 0 to 70      | LP324                   | <a href="#">Samples</a> |
| LP324DRG4        | ACTIVE        | SOIC         | D               | 14   | 2500        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | LP324                   | <a href="#">Samples</a> |
| LP324N           | ACTIVE        | PDIP         | N               | 14   | 25          | RoHS & Green    | NIPDAU                               | N / A for Pkg Type   | 0 to 70      | LP324N                  | <a href="#">Samples</a> |
| LP324PW          | ACTIVE        | TSSOP        | PW              | 14   | 90          | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | LP324                   | <a href="#">Samples</a> |
| LP324PWR         | ACTIVE        | TSSOP        | PW              | 14   | 2000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | LP324                   | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

- (3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.
- (4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.
- (5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.
- (6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device    | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LP2902DR  | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| LP2902PWR | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LP324DR   | SOIC         | D               | 14   | 2500 | 330.0              | 16.8               | 6.5     | 9.5     | 2.1     | 8.0     | 16.0   | Q1            |
| LP324DR   | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| LP324DRG4 | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| LP324PWR  | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal

| Device    | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-----------|--------------|-----------------|------|------|-------------|------------|-------------|
| LP2902DR  | SOIC         | D               | 14   | 2500 | 340.5       | 336.1      | 32.0        |
| LP2902PWR | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |
| LP324DR   | SOIC         | D               | 14   | 2500 | 364.0       | 364.0      | 27.0        |
| LP324DR   | SOIC         | D               | 14   | 2500 | 340.5       | 336.1      | 32.0        |
| LP324DRG4 | SOIC         | D               | 14   | 2500 | 340.5       | 336.1      | 32.0        |
| LP324PWR  | TSSOP        | PW              | 14   | 2000 | 356.0       | 356.0      | 35.0        |

**TUBE**


\*All dimensions are nominal

| Device   | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|----------|--------------|--------------|------|-----|--------|--------|--------|--------|
| LP2902D  | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| LP2902N  | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| LP2902PW | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| LP324D   | D            | SOIC         | 14   | 50  | 507    | 8      | 3940   | 4.32   |
| LP324N   | N            | PDIP         | 14   | 25  | 506    | 13.97  | 11230  | 4.32   |
| LP324PW  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |



D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  - Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AB.

D (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4211283-3/E 08/12

- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

# MECHANICAL DATA

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4040064-3/G 02/11

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

N (R-PDIP-T\*\*)

PLASTIC DUAL-IN-LINE PACKAGE

16 PINS SHOWN



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2022, Texas Instruments Incorporated