


**HIGH VOLTAGE ULTRA-FAST DIODE FOR VIDEO****MAJOR PRODUCT CHARACTERISTICS**

I_{Fpeak}	4 A
V_RRM	600 V
t_{rr}	55 ns
V_F (max)	1.2 V

FEATURES AND BENEFITS

- TURBOSWITCH™ OUTSTANDING BENEFITS.
- HIGH REVERSE VOLTAGE : 600 V
- LOW POWER LOSSES INDUCING LOW TEMPERATURE AND HIGH RELIABILITY.
- OPTIMIZED TRADE-OFF BETWEEN t_{rr} AND SOFTNESS FOR VIDEO HORIZONTAL DEFLECTION.

**DESCRIPTION**

High voltage ultra-fast diode especially designed for modulation and flyback rectification in standard and high resolution displays for TV's and monitors.

The device is packaged in a DO-201AD axial envelope.

ABSOLUTE RATINGS (limiting values)

Symbol	Parameter	VALUE	Unit
V _{RRM}	Repetitive peak reverse voltage	600	V
I _{F peak}	Forward peak current (1)	4	A
I _{FRM}	Repetitive peak forward current	100	A
I _{FSM}	Surge non repetitive forward current	80	A
T _{stg}	Storage temperature range	- 40 to 150	°C
T _j	Maximum operating junction temperature	150	°C

(1) on infinite heatsink with 10mm lead length

MDV04-600

THERMAL RESISTANCES

Symbol	Parameter	Max.	Unit
R _{th(j-l)}	Junction to lead	20	°C/W
R _{th(j-a)}	Junction to ambient on printed circuit L lead = 10mm	75	°C/W

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	Typ.	Max.	Unit
I _R *	Reverse leakage current	V _R = 480V T _J = 25°C T _J = 125°C		50 0.75	μA mA
V _F **	Forward voltage drop	I _F = 4 A T _J = 25°C T _J = 125°C		1.28 1.20	V V

Pulse test : * t_p = 5 ms, δ < 2%
** t_p = 380 μs, δ < 2%

DYNAMIC ELECTRICAL CHARACTERISTICS TURN-OFF SWITCHING

Symbol	Parameter	Test Conditions	Typ.	Max.	Unit
t _{rr}	Reverse recovery time	I _F = 0.5A I _R = 1A I _{rr} = 0.25A	55	75	ns
		I _F = 100 mA I _R = 100 mA I _{rr} = 10mA	130		ns

DYNAMIC ELECTRICAL CHARACTERISTICS TURN-ON SWITCHING

Symbol	Parameter	Test Conditions	Typ.	Max.	Unit
t _{fr}	Forward recovery time	I _F = 4 A dI _F /dt = 100 A/μs Measured at 1.1 x V _F max. T _J = 25°C		0.5	μs
V _{FP}	Peak forward voltage				15

To evaluate the maximum conduction losses use the following equation :

$$P = \frac{1.0 \times I_p}{2} \times \delta + \frac{0.050 \times I_p^2}{3} \times \delta$$

δ : duty cycle
I_p : Peak current

Ex : for I_p = 4 A and δ = 0.5, P = 1.2 Watts.

Fig. 1: Power dissipation versus peak forward current (triangular waveform, $\delta=0.5$).




Fig. 2: Relative variation of thermal impedance junction to ambient versus pulse duration (epoxy printed circuit board, $e(\text{Cu})=35\mu\text{m}$), recommended pad layout).




Fig. 3: Forward voltage drop versus forward current (maximum values).




Fig. 4: Reverse recovery time versus dIF/dt .




Fig. 5: Transient peak forward voltage versus dIF/dt .






Fig. 6: Forward recovery time versus dIF/dt .



MDV04-600

PACKAGE MECHANICAL DATA DO-201AD



REF.	DIMENSIONS				NOTES
	Millimeters		Inches		
	Min.	Max.	Min.	Max.	
A		9.50		0.374	1 - The lead diameter $\varnothing D$ is not controlled over zone E 2 - The minimum axial length within which the device may be placed with its leads bent at right angles is 0.59" (15 mm)
B	25.40		1.000		
$\varnothing C$		5.30		0.209	
$\varnothing D$		1.30		0.051	
E		1.25		0.049	

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
MDV04-600	MDV04-600	DO-201AD	1.166g.	600	Ampopack
MDV04-600RL	MDV04-600	DO-201AD	1.166g.	1900	Tape & reel

- Epoxy meets UL94,V0
- Polarity : Cathode indicated by polarity band

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>